

Matrix® Pneumatic Speed delivers even faster production times than our standard systems.

KEY FEATURES

- Pneumatic pressure
- Easy-to-use control panel
- Anti-curl technology
- Semi-automatic feed
- Automatic pneumatic separator

GREAT FOR USE IN

- Commercial printers
- Digital printers
- Copy and print shops
- Inplant print rooms

IDEALLY SUITED FOR

- Business cards
- Menus
- Book covers
- Brochures
- Flyers

and many more...

Scan with your smartphone to watch the video



 /vividlaminating

 @vividlaminating

 /vividlaminating



PNEUMATIC 

▲ MX-530S with OMNI-530



Design

The Matrix Pneumatic Speed can run up to 20 Meters/Minute. Printers can laminate work even faster to get the job finished and back to the customer.

Pneumatic pressure rollers allow you to laminate certain substrates up to 50% quicker, saving both time and cost.

The Pneumatic option is produced in Britain which shortens our supply chains and lead times. We've used the highest quality components within the systems, including Omron switches and Schneider electrics.

The Matrix Pneumatic Speed has the ability to fit an Omni-Flow system.

Specifications

MX-530PS

Max. Mechanical Speed (m/ft/min)	20m/65ft
Max. Lamination Film Width (mm/inches)	510mm/20"
Paper Thickness (gsm/lbs)	135gsm +/-90lbs +
Maximum Sheet Width (mm/inches)	550mm/22"
Warm-up Time (mins)	under 10
Temperature Range (°C/°F)	0-140°C/32-284°F
Power Supply (V)	220/240
Power Supply Required (Amps)	32
Power Consumption (W)	5000
Overall Dimensions (mm/inches)	900x2050x1400mm/35x81x55"
Gross Machine Weight (Kg/lbs)	275kg/605lbs
Warranty*	1 Year

*For full terms & conditions on parts and labour warranty, visit vivid-online.com/support/warranty_information

Vivid Laminating Technologies Ltd

Matrix House, Norman Court, Ivanhoe Business Park,
Ashby de la Zouch, Leicestershire LE65 2UZ England

+44 (0)845 1 30 40 50 sales@vivid-online.com

vivid-online.com

Vivid care about the environment and is an ISO 14001 registered company.