

**KEY FEATURES** 

seperator

Pneumatic pressure

Anti-curl technology

• Semi-automatic feed

· Automatic pneumatic

**GREAT FOR USE IN** 

Digital printers

Commercial printers

· Copy and print shops

Inplant print rooms

• Easy-to-use control panel

# MATRIX®

## PNEUMATIC SPEED LAMINATING SYSTEM

Matrix® Pneumatic Speed delivers even faster production times than our standard systems.



 Business cards Menus

**IDEALLY SUITED FOR** 

- Book covers
- Brochures
- Flyers

and many more...

Scan with your smartphone to watch










Design

The Matrix Pneumatic Speed can run up to 20 Meters/Minute. Printers can laminate work even faster to get the job finished and back to the customer.

the highest quality components within the systems, including Omron switches and Schneider electrics.

The Matrix Pneumatic Speed has the ability to fit an Omni-Flow system.



Specifications	MX-530PS
Max. Mechanical Speed (m/ft/min)	20m/65ft
Max. Lamination Film Width (mm/inches)	510mm/20"
Paper Thickness (gsm/lbs)	135gsm +/90lbs +
Maximum Sheet Width (mm/inches)	550mm/22"
Warm-up Time (mins)	under 10
Temperature Range (°C/°F)	0-140°C/32-284°F
Power Supply (V)	220/240
Power Supply Required (Amps)	32
Power Consumption (W)	5000
Overall Dimensions (mm/inches)	900x2050x1400mm/35x81x55
Gross Machine Weight (Kg/lbs)	275kg/605lbs
Warranty*	1 Year

#### **Vivid Laminating Technologies Ltd**

Matrix House, Norman Court, Ivanhoe Business Park, Ashby de la Zouch, Leicestershire LE65 2UZ England







**KEY FEATURES** 

seperator

Pneumatic pressure

Anti-curl technology

· Semi-automatic feed

Automatic pneumatic

**GREAT FOR USE IN** 

Digital printers

Commercial printers

Copy and print shops

**IDEALLY SUITED FOR** 

Business cards

 Book covers Brochures

and many more..

Scan with your

smartphone to watch

vividlaminating

Menus

Flyers

Inplant print rooms

• Easy-to-use control panel

# MATRIX®

## PNEUMATIC SPEED LAMINATING SYSTEM

Matrix® Pneumatic Speed delivers even faster production times than our standard systems.



### ▲ MX-530S with OMNI-530 Reverse

Pneumatic



### Design

The Matrix Pneumatic Speed can run up to 20 Meters/Minute. Printers can laminate work even faster to get the job finished and back to the customer.

Pneumatic pressure rollers allow you to laminate certain substrates up to 50% quicker, saving both time

The Pneumatic option is produced in Britain which shortens our supply chains and lead times. We've used the highest quality components within the systems, including Omron switches and Schneider electrics.

The Matrix Pneumatic Speed has the ability to fit an Omni-Flow system.



MX-530PS
20m/65ft
510mm/20"
135gsm +/90lbs +
550mm/22"
under 10
0-140°C/32-284°F
220/240
32
5000
900x2050x1400mm/35x81x55"
275kg/605lbs
1 Year

### **Vivid Laminating Technologies Ltd**

Matrix House, Norman Court, Ivanhoe Business Park, Ashby de la Zouch, Leicestershire LE65 2UZ England



+44 (0)845 1 30 40 50 sales@vivid-online.com

Vivid care about the environment and is an ISO 14001 registered company.



Vivid care about the environment and is an ISO 14001 registered company